Interlocking Concrete Paving Stones





Roman

Our Roman pavers provide unlimited design possibilities as you can mix and match the three sizes and the many color options to create a truly one-of-a-kind design!

Thickness: Stocked in 60 mm. 80 mm available by special-order.

Our traditional Roman has the smooth pillow-top texture, but we can texture. Please call our Sales Department for pricing and availability of Slate-top textured Roman pavers.





5 7/1

Roman I



Magnum

Roman II

I ackagi	ing for Rollia	I and Luio-	GOUDIC.
Shape	Pieces per	Stones per	Square feet
1	square foot	pallet	per pallet
Roman I	3.17	370	117
Roman II	4.76	560	118
Magnum	1.63	180	110

Sandstone Blend

Joint Patterns for Roman and Euro-Cobble View additional patterns on our website



Combo Herringbone 60% Roman I 40% Roman II



I Pattern

75% Roman I

25% Roman II

Roman and Euro-Cobble Patterns Using the Magnum View additional patterns on our website

1-1-1 2-2-2

Herringbone Pattern Pattern 27.2% I's 27.1% I's 18.6% II's 18.7% II's 54.2% Magnum's 54.2% Magnum's


c									
	Π	_	F	+	_		┣	-	1
				L			_	1	
			-	-					
		⊢	<u> </u>	_					i
		1			_				-
	T	-					-	-	
_	ᅡ		-				-	Г	1
								⊢	
-	Γŀ	_							
_	ш					_		1	

3-1-2 Herringbone Pattern 39% I's 9% II's 52% Magnum's





Colors Stock colors subject to change. Be sure to view actual product samples prior to ordering!



Stocked in Magnums

and I's only



Sandstone Blend

Grey/Charcoal Blend



Brown/Charcoal Blend

Coastal Moss Special-order



Sienna Brown

Dark Brown Special-order



Cream Brown





Cambria Gold



Lopez Blend



Railroad Blend



Carmel Brown



Morro Bay Grey



See Canyon Red



Cerro Blend

TABLE OF CONTENTS

Roman inside cover an	d 1
Euro-Cobble	2
Old World Cobble	3
Tri-Cobble	4
Circle Cobble	5
Balboa	6
FlagStone	7
Chumash	8
Holland	9
Apache	10
Centurion	11
Eco-Perm, Turfpaver,	
Paver Accessories	12
Permeable Roman	13

While all efforts were made to show product colors and textures as accurately as possible, actual product may vary from that shown in this brochure. Always request actual product color samples prior to ordering.

Detailed installation and specification information is available from our sales office, or from our website at airvolblock.Com.

EURO-COBBLE

Mixture of Brown/Charcoal Blend and Sandstone Blend

Our Euro-Cobble pavers are textured and tumbled to replicate the appearance of hand-crafted natural stone pavers. Use a single size or mix two or three sizes to create beautiful patterns!

Create a truly unique project by blending multiple colors.

Thickness: Stocked in 60 mm. 80 mm available via special-order.

Packaging: Refer to previous "Roman" page for packaging.

Joint Patterns: Refer to previous "Roman" page for Euro-Cobble joint patterns.

Magnum

8 1/4

10 7/8"

5 7/16"

Colors Stock colors subject to change. Be sure to view actual product samples prior to ordering!









Euro-Cobble II

5 7/16"



Euro-Cobble with Magnums

Grey/Charcoal Blend Brown/Charcoal Blend Dark Brown

Cream Brown





OLD WORLD COBBLE

Smooth Side Up Brown/Charcoal Blend

Our unique Old World Cobble is a mixture of seven irregular shapes which are tumbled to replicate the weathered appearance of genuine European stone pavers. Approximate size ranges from 2" x 4" to 4" x 6". Each Old World paver has a smooth side and a textured side. This paver style can be installed with either all the smooth surfaces facing up or all of the textured surfaces facing up.

Thickness: Stocked in 60 mm. 80 mm available by special order. Packaging for 60 mm: 96 sq. ft. per pallet. 80 mm: 70 sq. ft. per pallet.

This shape is not recommended for use in vehicular traffic areas. Polymeric Sand is recommended for use with Old World Cobble.

Colors Stock color selection subject to change. Be sure to view actual product samples prior to ordering! The 3 samples below show the smooth side facing up.








Grey/Charcoal Blend Special-order

Brown/Charcoal Blend

Sandstone Blend

Smooth Side Up Sandstone Blend




Our Tri-Cobble paver is a preblended mixture of three different sizes. Important Note: The individual pieces are not sold separately, so please be sure to install them in these approximate proportions: 5 Large Rectangles to 5 Squares to 2 small rectangles.

The rounded sides of the Tri-Cobble are conducive to creating gracefully sweeping curves.

Thickness: Stocked in 60 mm.

Packaging: 122 square feet per pallet.






Mixture of Brown/Charcoal Blend and Sandstone Blend

Colors (Tri-Cobble and Circle Cobble) Stock color selection subject to change. Be sure to view actual product samples prior to ordering!



TRI-COBBLE

Red/Charcoal Blend Charcoal



Special order



Grey/Charcoal Blend Brown/Charcoal Blend Sunburst Blend



Sandstone Blend

CIRCLE COBBLE

Use as a focal point within any style of pavers.

Pre-packaged in individual 71-1/4" diameter kits. Larger circles can be made by adding additional rings of our Tri-Cobble pavers.

Thickness: Stocked in 60 mm.

Ring 13

Packaging: One 71-1/4" circle per pallet (Approximately 27.7 square feet). Pallets of Circle Cobble may include a few extra unneeded pieces due to the mold configuration. Don't be alarmed if you have a few pieces left over!


Stock Colors Swatches: Same as Tri-Cobble Colors

Installation Chart

Circle Kit

Ring #	Pieces Required	Paver Shape	Notes	Approx. Diameter (in inches)	Additional sq.ft of Tri-Cobble needed
Center	2 Center Pieces			4 5/8	0
Ring 1	8 Wide Wedges	\bigtriangledown		15	0
Ring 2	7 Wide Wedges 7 Squares		Alternate Wide Wedge and Squares	24 3/8	0
Ring 3	22 Narrow Wedges		All Narrow Wedges	33 3/4	0
Ring 4	29 Narrow Wedges	\Box	All Narrow Wedges	43 1/8	0
Ring 5	17 Narrow Wedges 17 Squares		Alternate 1 Square to 1 Narrow Wedge	52 1/2	0
Ring 6	21 Narrow Wedges 20 Squares		Alternate 1 Square to 1 Narrow Wedge	61 7/8	0
Ring 7	32 Narrow Wedges 16 Squares		Alternate 1 Square to 2 Narrow Wedges	71 1/4	0
			Optional Rings		
		Create additiona	al rings by using Tri-Cobble Pavers		
Ring 8	Use the 3 Tri-C	obble shapes to a	create the optional rings	80 5/8	8.2
Ring 9		"		90	17.4
Ring 10		"		99 3/8	27.5
Ring 11		"		108 3/4	38.5
Ring 12		"		118 1/8	50.6





Square

ed/Charcoal Blend

127 1/2

63.5

4 3/4" 4 3/4

Center Piece



Pallets of Circle Cobble may include a few extra unneeded pieces due to the mold configuration. You will have pieces left over.

BALBOA

Our Balboa Paver lends itself to the creation of many interesting patterns.

Create a truly unique project by blending multiple colors.

Stocked in 60 mm thickness.

Various Blends

Patterns



Fish Scale







Monarch

Colors (Stock color selection subject to change) Be sure to view actual product samples prior to ordering!




Sunburst Blend





Brown/Charcoal Blend



The FlagStone paver makes it easy to create patios and walkways with a random stone appearance. Mix and match colors to create a visually striking surface!

Thickness: 70 mm.

Packaging: 75 sq. ft. per pallet.




Sandstone



Sienna Brown



Sunburst



Colors

Stock color selection subject to change. Be sure to view actual product samples prior to ordering!



CHUMASH

Special-order only. The delightful combination of two geometric shapes makes our Chumash paver pleasing to the eye!

Thickness: Made in 60 mm only.

Coverage: 3.4 pieces per square foot.

Packaging: 118 square feet per pallet.




Red/Charcoal Blend

Joint Patterns



Basket Weave





Herringbone



Runner

Colors This product is made-to-order. Call our Sales Department for pricing. Be sure to view actual product samples prior to ordering.





Grey Special order





Red/Charcoal Blend Special order

Sunburst Blend Special order

HOLLAND

This original paver shape has been utilized world-wide for decades!

The Holland paver can be used by itself, or as a distinctive border around any of the other paver shapes!

> Thickness: Stocked in 60 mm. 80 mm available via special-order.



Tumbled Holland

Large photo, Red color

							_
		_					
-	С	 1-	at	TA	Ta	 ~	


Basket Weave

F

-

				-			
					_		
							_
H	er	riı	ng	bo	on	e	

Running Bond



Colors Stock color selection subject to change. Be sure to view actual product samples prior to ordering!









Red/Charcoal Blend Special order



Sunburst Blend Special order

APACHE

Our distinctive Apache paver shape has been widely used for over three decades!

Thickness: Stocked in 60 mm. 80 mm available via special-order.

Coverage: 3.9 pieces per square foot.

Packaging: 105 square feet per pallet.






Tan Special order

1

Red/Charcoal



CENTURION

Our Centurion paver provides clean lines and easy installation!


> Thickness: Stocked in 60 mm.

Coverage: 1.07 pieces per square foot.


Packaging: 115 square feet per pallet.

Sandstone Blend

Joint Patterns



Stack Bond



Running Bond

Plaza Weave 82% Centurion, 18% Roman II Due to it's size, the Centurion is considered to be a paving slab rather than a paving stone. The Centurion has a compressive strength of 5,000psi.


Colors Stock color selection subject to change. Be sure to view actual product samples prior to ordering!







11 3/4"



Sandstone Blend

Charcoal Special order

11 3/4



ECO-PERM & TURFPAVER

Planting grass in these types of pavers creates islands of cooling within the urban landscape, while allowing water to easily permeate the pavement.

- Many possible uses:
- · Cart Paths
- Driveway Extensions
- Embankment Erosion Control
- Pathways



- Emergency Access Roads
- Environmentally Friendly
- Parking Areas
- · Allows Air & Water to Tree Roots



ECO-PERM shown above

Because of the large void spaces created by the Eco-perm, they are recommended for use only in areas subject to vehicular access like fire access lanes. For permeable areas subject to pedestrian traffic, we recommend that you use the Permeable Roman pavers as shown on page 13. Thickness: 80 mm.

Coverage: 2.9 pieces per square foot based upon minimal joint pattern. Packaging: 83 square feet per pallet based upon minimal joint pattern.


Eco-Perm is a special-order item



Brown/Charcoal Blend Grey Be sure to view actual product samples prior to ordering!



Full Open 18.3% void Requires 2.6 pcs/sq.ft.



Running Bond

Requires 2.9 pcs/sq.ft.

10.5% void







Minimal 7.9% void Requires 2.9 pcs/sq.ft.


TURFPAVER shown at right

Our Turfpavers are manufactured with 5,000 psi concrete and comply with ASTM C-1319 Standard Specification for Concrete Grid Pavements. Please be aware that Turfpavers are prone to cracking during the compaction process. This is normal and does not affect their performance.




Grey

A PS SMO



Be sure to view actual product samples prior to ordering!





WE ALSO STOCK A COMPLETE LINE OF PAVER ACCESSORIES

- Polymeric Joint Sand (see APS below)
- Edge Restraint
- Paver Sealers and Cleaners
- Construction Adhesives
- Paver Lights

AIR VOL POLYMERIC SAND (APS) FOR PAVER JOINTS

- Resists Weed Growth, Insects, Erosion
- Stabilizes Pavers
- Non-Staining Formula
- · Made in USA









Alternating 11.7% void Requires 2.8 pcs/sq.ft. Create beautiful, functional pavements while effectively managing storm water run-off using the Permeable Roman paver! Choose from standard smooth, Slatetop, or Tumbled Slate-top textures. Please call our Sales Office to check on color and texture availability. Our Permeable Roman pavers can also be integrated with our standard Roman Paver (see page 1) to provide selective areas of permeability.


Paver Sizes include the width of 1 spacer nub



Permeable Roman I



Permeable Roman II



Magnum Permeable Roman




Spacers protrude .29" (7.5 mm) from the main body

Joint Patterns for Roman Permeable Pavers View additional patterns on our website





I Pattern 75% Roman I 25% Roman II




Void Area: minimum of 6.8% void Thickness: 80 mm. Packaging:

Permeable Roman I: 93 sq. ft. per pallet Permeable Roman II: 94 sq. ft. per pallet

- A typical permeable base is constructed using these materials:
- A sub-base of number 2 stone (or approved equal)
- A base of number 57 stone (or approved equal)
- A 1-1/2" to 2" thick bedding course of number 8 stone (or approved equal)
- Joints filled with number 8 stone (or approved equal)

Consult with a civil engineer for determination of required base and sub-base depths. Cast concrete or pre-cast concrete curbs are recommended for use as the edge restraint on open-graded bases.

Roman Patterns Using the Magnum View additional patterns on our website



 1-1-1
 2-2-2

 Pattern
 Herringbone

 27.2% I's
 Pattern

 18.6% II's
 27.1% I's

 54.2% Magnum's
 18.7% II's

 54.2% Magnum's
 54.2% Magnum's



3-1-2 Herringbone Pattern 39% I's 9% II's 52% Magnum's





Scan this tag to visit our website





#1 Suburban Rd. San Luis Obispo, CA 93401 Tel: 805-543-1314 Fax: 805-543-0848 www.airvolblock.com

JUNE 2016